

250 HP Pro XS

\$47,690



Description

Mercury 250hp Pro XS - Fully Fitted

\$47,690 incl GST

Auckland Marine Centre - Offer ends 2026-11-08 Mercury 0% Interest Over 5 Years **Finance Application:**

<https://online.udc.co.nz?embed=true&uid=6e64ad&newResizer=1>

The 250hp Pro XS provides hard-charging performance to put you out front and keep you there. Pro XS is the choice of tournament anglers and performance enthusiasts who don't like coming second. Mercury V-8 Pro XS models transform every drop of fuel into performance delivering class leading fuel economy at cruising speed and wide-open throttle. Advanced Range Optimisation (ARO) utilises closed-loop fuel control to precisely adjust the fuel mixture and deliver the best possible efficiency. All Pro XS FourStroke models now come with a 3+3=6 Year factory warranty. **ENGINE**

DETAILS

Great for bass and multi-species fishing boats. **SPECIFICATIONS - 250**

HP / kW	250 / 186
Engine type	V-8
MidSection	Conventional MidSection
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	5600-6200
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum



Recommended oil NMMA Certified FCW SAE 10W-30
Engine protection operator warning system SmartCraft Engine Guardian
Compatible with SmartCraft digital technology Yes
Starting Electric Start with SmartStart Protection
Controls Remote Mechanical or Digital Throttle & Shift (DTS)
Steering Big Tiller (optional) Hydraulic (standard) Power (optional)
Shaft length 20" / 508 mm 25" / 635 mm
Gearcase ratio 1.75:1
Dry weight *Lightest model available 505 lbs / 229 kgs
CARB star rating 3
Bore and stroke 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition SmartCraft PCM 112 Digital Inductive
Cooling system Water-cooled with thermostat
Gear shift F-N-R
Gearcase options 20": TorqueMaster 25": 5.44"
Trim system Power trim and tilt
Exhaust system Through prop
Color Phantom Black
Lubrication system Integrated wet sump
Oil Capacity 7.0 Quarts / 6.6 Liters
Maximum Trim Range 20° (-6° to 14°)
Maximum Tilt Range 73° (-6° to 67°)

