

300 HP Sea Pro

\$51,558.00



Description

The new Mercury V-8 SeaPro outboard models bring more of everything to the job—more displacement, more power, more efficiency and more durability. The impressive muscle of our new V-8 4.6-litre powerhead is specifically designed for commercial duty and delivers our best-ever fuel economy and FourStroke performance. The combination of ample torque and low weight makes these engines ideal for heavily-loaded boats. Guaranteed to do its job, so you can do yours. Mercury SeaPro FourStroke models come with a 2+1 = 3 year commercial factory warranty. **ENGINE DETAILS**

Advanced Range Optimization (ARO) and closed-loop fuel control work together to precisely adjust the fuel mixture for optimal fuel economy. For commercial fishing vessels, commercial workboats and law-enforcement boats. **SPECIFICATIONS - 300 CMS**

HP / kW	300/224
Engine type	V-8
MidSection	Conventional MidSection
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	4800-5600
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 25W-40 (Optional 10W-30 for Cold Conditions)
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric Start with SmartStart Protection
Controls	Remote Mechanical or Digital Throttle & Shift (DTS)
Steering	Hydraulic (standard) Power (optional)
Shaft length	20" / 508 mm 25" / 635 mm 30" / 762 mm



Gearcase ratio 1.75:1
Dry weight *Lightest model available 527 lbs / 239 kgs
CARB star rating 3
Bore and stroke 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition SmartCraft PCM 112 Digital Inductive
Cooling system Water-cooled with thermostat
Gear shift F-N-R
Gearcase options 5.44"
Trim system Power trim and tilt
Exhaust system Through prop
Counter Rotation Available
Color Phantom Black
Lubrication system Integrated wet sump
Oil Capacity 7.0 Quarts / 6.6 Liters
Maximum Trim Range 20° (-6° to 14°)
Maximum Tilt Range 73° (-6° to 67°)

