

Mercury 115 HP EFI Fourstroke

POA



Description

Mercury 115 HP EFI Fourstroke - Unbridled power, unexpectedly compact, uncompromising reliability, unbelievable fuel efficiency. Unlike any other mid-range Fourstroke the world has ever seen.

HP / kW	115 / 84.6
Engine type	8-valve single overhead cam (SOHC) Inline 4
Displacement (L)	2.1
Full throttle RPM	5000-6000
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	35 amp / 441 watt with water-cooled voltage regulator
Recommended fuel	Unleaded 91 RON Minimum
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Smart Start Electric
Controls	Mechanical throttle & shift
Steering	Big Tiller Compatible Dual Cable Mechanical Hydraulic power steering
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	2.07:1
Dry weight *Lightest model available	359 lbs / 163 kg
Emissions Star Rating	3
Bore and stroke	3.5 x 3.2" / 90 x 81 mm



Ignition	SmartCraft ECM 70 Digital Inductive	
Fuel system	Electronic Fuel Injection (EFI)	
Cooling system	Water-cooled with thermostat	
Gear shift	F-N-R	
Gearcase options	Standard	
Trim system	Power Tilt	Power Trim
Exhaust system	Through prop	
Shallow water trim range (degrees)	20	
Color	Phantom Black	
Lubrication system	Integrated Dry Sump	
Oil Capacity	5.5 qts / 5.2 l	
Maximum Trim Range	22° (-6° to 16°)	
Maximum Tilt Range	70° (-6° to 64°)	

