## Mercury 115 Pro XS Fourstroke \$22,801.00



## Description

Incredible power, combined with light weight, gives you mind-blowing performance. Mercury's new 115hp Pro XS FourStroke redefines outboard performance.

Choice of Champions.

Pro XS is the best-selling tournament fishing outboard in the world, and has powered more competitive anglers to victory than any other engine. Run with the same confidence professional tournament anglers have – trust Pro XS.

Keeps your battery charged.

The Idle Charge feature monitors your battery $\hat{a} \in \mathbb{T}^{M}$ s voltage state, and will increase the engine rpm in order to provide up to 48% more battery charging at idle. This supports the greater power demands of today $\hat{a} \in \mathbb{T}^{M}$ s sophisticated marine electronics and accessories, letting boaters and anglers safely stay out on the water longer.

Performance.

Incredible power, combined with light weight, gives you mind-blowing performance. Optional larger Command Thrust gearcase delivers even more control for boats that sit lower in the water.

Exclusive Versatility.

Two exclusive features give the 115 Pro XS the versatility to outperform on a wide range of applications.



Available in two shaft lengths - 20" and 25" - this engine is an ideal option for a wide range of freshwater and saltwater boats.

The Command Thrust model, compatible with Mercury's larger-diameter propellers, helps quickly lift heavy boats onto plane and hold them there at lower speeds.

HP/kW - 115/86 Engine type - 8-valve single overhead cam (SOHC) Inline 4 Displacement (L) - 2.1 Full throttle RPM - 5300-6300 Air induction - Performance-Tuned Scroll Intake Manifold Fuel induction system - Computer Controlled Multi-Port Electronic Fuel Injection (EFI) Alternator amp / Watt - 35 amp / 441 watt with water-cooled voltage regulator Recommended fuel - Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum Recommended oil - NMMA Certified FCW SAE 10W-30 Engine protection operator warning system - SmartCraft Engine Guardian Compatible with SmartCraft digital technology - Yes Electric (turn-key) Starting -Smart Start Electric Controls - Mechanical throttle & shift Steering - Dual Cable Mechanical Hydraulic power steering Shaft length - 20" / 508 mm 25" / 635 mm Gearcase ratio - 2.07:1 Dry weight \*Lightest model available - 359 lbs / 163 kg Bore and stroke - 3.5 x 3.2 /90 x 81 Ignition - SmartCraft ECM 07 Digital Inductive Fuel system - Electronic Fuel Injection (EFI) Cooling system - Water-cooled with thermostat Gear shift - F-N-R Gearcase options - Standard



## Trim system - Power Tilt Power Trim

- Exhaust system Through prop
- Color Phantom Black
- Lubrication system Wet sump
- Oil Capacity 5.5 qts / 5.2 l
- Maximum Trim Range 22° (-6° to 16°)
- Maximum Tilt Range 70Ű (-6Ű to 64Ű)