

Mercury 150 HP Fourstroke

POA



Description

Mercury 150 HP Fourstroke - The innovation behind this 150hp FourStroke has come directly from you, our customer.

HP / kW	150 / 110		
Engine type	8-valve single overhead cam (SOHC)		Inline 4
Displacement (L)	3.0		
Full throttle RPM	5000-5800		
Air induction	Performance-Tuned Scroll Intake Manifold		
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)		
Alternator amp / Watt	60 amp / 756 watt (Belt-Driven)		
Recommended fuel	Unleaded 91 RON Minimum		
Recommended oil	Mercury FourStroke Oil 10W-30		
Engine protection operator warning system	SmartCraft Engine Guardian		
Compatible with SmartCraft digital technology	Yes		
Starting	Electric (turn-key)	Smart Start Electric	
Controls	Mechanical throttle & shift		
Steering	Big Tiller Compatible	Dual Cable Mechanical	Electro-Hydraulic Power Steering Optional on Duals Hydraulic power steering
Shaft length	20" / 508 mm	25" / 635 mm	
Gearcase ratio	1.92:1		
Dry weight *Lightest model available	455 lbs / 206 kg		
Emissions Star Rating	3		
Bore and stroke	4.0 x 3.6" / 102 x 92 mm		



Ignition	SmartCraft ECM 70 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim system	Power Tilt Power Trim
Exhaust system	Through prop
Counter rotation	Available
Color	Phantom Black
Lubrication system	Integrated Dry Sump
Oil Capacity	6.3 qts / 6.0l
Maximum Trim Range	22° (-6° to 16°)
Maximum Tilt Range	73° (-6° to 67°)

