Mercury 250 HP Verado

Was $53,232, Now $50,600



Description

The 250hp Verado premium outboard redefines the category with advanced engineering, innovative technology and refined operation. Representing the pinnacle of superior outboard design and performance Verado is unrivalled on the water. Built to power the largest boats for the boldest adventures, Verado engines boast advanced engineering and refined operation for boat owners who refuse to compromise. Every Verado feature is designed to deliver the ultimate, most satisfying on-water experience. The smooth, refined power of a V-8 4.6-litre powerhead delivers exhilarating acceleration and top speed to run offshore with confidence. Generous displacement and robust design provide uncompromising durability and reliability. The Mercury-exclusive Advanced MidSection (AMS) and under-cowl noise management features set the standard for smooth, quiet marine propulsion. Verado models now come with a 3+3=6 Year factory Warranty. ENGINE DETAILS

Built tough to withstand the rigors of saltwater operation, no outboard in the class offers more displacement. Great for deck, inflatable rigid hull, inshore fishing, multi-species fishing, offshore fishing, and runabout cuddy boats and tritoons. SPECIFICATIONS - 250

HP / kW	250 / 186
Engine type	V-8
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	5200-6000
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	115-amp (1449 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Starting	Electric Start with SmartStart Protection
Controls	Standard: Digital Throttle & Shift (DTS)
Steering	Integrated Electro-Hydraulic Power-Steering

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ

Shaft length	20" / 508 mm 25" / 635 mm 30" / 762 mm
Gearcase ratio	1.85:1
Dry weight *Lightest model available	600 lbs / 272 kgs
CARB star rating	3
Bore and stroke	3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	SmartCraft PCM 112 Digital Inductive
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	5.44"
Trim system	Power trim and tilt
Exhaust system	Through prop
Color	Cold Fusion White Pearl Fusion White Phantom Black Warm Fusion White
Oil Capacity	7.0 Quarts / 6.6 Liters
Maximum Trim Range	20Â° (-6Â° to 14Â°)
Maximum Tilt Range	73Â° (-6Â° to 67Â°)