

# Mercury 3.5 HP Fourstroke

## POA



## Description

Mercury 3.5 HP Fourstroke - With models ranging from 30hp to 2.5hp, the Mercury FourStroke Portable are suited to everything from small inflatables to aluminium dinghies and punts. Mercury's FourStroke Portables are designed with leading edge features for enhanced reliability and performance.

HP / kW	3.5 / 2.6
Engine type	1 cylinder
Displacement (CID/CC)	5.2 / 85
Full throttle RPM	5000-6000
Fuel induction system	2-valve pushrod (overhead valve)
Recommended fuel	87% octane / up to 10% ethanol
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	Over-rev
Starting	Manual
Steering	Tiller with 360° turning
Shaft length	15" / 381 mm    20" / 508 mm
Gearcase ratio	2.15:1
Dry weight *Lightest model available	38 lbs / 17 kg
CARB star rating	3
Emissions Star Rating	3
Bore and stroke	2.16 x 1.42" / 55 x 36 mm
Ignition	CDI w/electronic spark advance



Fuel system Carbureted  
Cooling system Water-cooled with thermostat  
Gear shift F-N  
Gearcase options Standard  
Trim system 4 position  
Trim positions 4  
Exhaust system Above prop  
Shallow water trim range (degrees) 16  
Integrated fuel tank (gal / L) 0.3 / 1.1  
Color Phantom Black

