

# Mercury 5HP Two Stroke

\$1,949



## Description

**Mercury's lightest model is at only 57 lbs. (26. Kgs.).** These engines are easy for customers to transport with its **Ergonomic Carrying Handle**. For ease in mounting to transom or motor bracket are the several gripping points on the rear of engine. One of the Lightest in its Class!

HP/kW @ Prop

5 / 3.7

Max RPM (WOT)

4500 - 5500

Induction System

2-valve Push Rod (OHV)

Fuel System

Carbureted

Alternator Amp/Watt

4/50 amp on select models

Starting

Manual

Gear Shift

F-N-R

Steering

Tiller

Recommended Oil

Mercury 4-Stroke Outboard Oil

Cooling System

Water-Cooled w/ thermostat



Cylinders

1

Displacement (CID/cc)

7.5 / 123

Bore X Stroke (in/mm)

2.32 x 1.77 / 59 x 45

Ignition System

CDI w/ electronic spark advance

Gear Ratio

2.15:1

Propeller

8.375" x 8"

Trim Positions

6

Shallow Water Drive

Standard

Exhaust System

Through Prop

Fuel/Ethanol Tolerance

87 octane/up to 10% Ethanol

Integral Fuel Tank (gal/L)

0.30 / 1.0 (Optional 3.3 /12 Remote)

Operator Warning System

Low Oil Pressure, Over-rev

SmartCraft Technology

No

Shaft Length (in/mm)

15/381 20/508 25/635

Dry Weight (lbs/kg)\*

57/26 \*Lightest model available

