

Mercury 6hp 4 stroke Outboard

\$1999.00



Description

Key Specifications

Model Example: Mercury 6 HP FourStroke (e.g., model 6MH) Mercury 6 HP 4 Stroke Outboard

Power: 6 hp (4.4 kW)

Engine Type: Single cylinder, 4-stroke

Displacement: 123 cc (7.5 cu in)

Full Throttle RPM: 5,000–6,000 rpm

Fuel Induction: 2-valve pushrod (overhead valve)

Recommended Fuel: 87 octane gasoline, up to 10% ethanol

Recommended Oil: Mercury FourStroke Oil 10W-30

Ignition: CDI (capacitor discharge) with electronic spark advance

Bore x Stroke: 2.32 in — 1.77 in (59 mm — 45 mm)

Cooling System: Water-cooled with thermostat

Gear Shift: Forward-Neutral-Reverse (F-N-R)

Gearcase Ratio: 2.15:1

Trim Positions: 6 trim angles

Shallow Water Drive: Yes; shallow water trim range ~16°

Exhaust System: Through-prop (i.e., exhaust exits under the prop)

Fuel Tank:

Integrated: ~1.1 L (0.3 gal)

Optional Remote Tank: ~12 L (3.2 gal)

Steering: Tiller handle

Starting: Manual pull start



Dry Weight: ~26 kg (57 lb) for the lightest model

Carb Star / Emissions Rating: CARB 3-star, Emissions 3-star (depending on region)

Color: Phantom Black (typical)

Alternator (optional): 12 V / 50 W (on some models)

