

Mercury 75 HP EFI Fourstroke

POA



Description

Mercury 75 HP EFI Fourstroke - Unbridled power, unexpectedly compact, uncompromising reliability, unbelievable fuel efficiency. Unlike any other mid-range Fourstroke the world has ever seen.

HP / kW	75 / 56		
Engine type	8-valve single overhead cam (SOHC)	Inline 4	
Displacement (L)	2.1		
Full throttle RPM	4500-5500		
Air induction	Performance-Tuned Scroll Intake Manifold		
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)		
Alternator amp / Watt	35 amp / 441 watt with water-cooled voltage regulator		
Recommended fuel	Unleaded 91 RON Minimum		
Recommended oil	Mercury FourStroke Oil 10W-30		
Engine protection operator warning system	SmartCraft Engine Guardian		
Compatible with SmartCraft digital technology	Yes		
Starting	Smart Start Electric		
Controls	Mechanical throttle & shift		
Steering	Big Tiller Compatible	Dual Cable Mechanical	Hydraulic power steering
Shaft length	20" / 508 mm		
Gearcase ratio	2.07:1		
Dry weight *Lightest model available	359 lbs / 163 kg		
Emissions Star Rating	3		
Bore and stroke	3.5 x 3.2" / 90 x 81 mm		



Ignition	SmartCraft ECM 70 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim system	Power Tilt Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	20
Color	Phantom Black
Lubrication system	Integrated Dry Sump
Oil Capacity	5.5 qts / 5.2 l
Maximum Trim Range	22° (-6° to 16°)
Maximum Tilt Range	70° (-6° to 64°)

