

Mercury 75 HP Sea Pro Fourstroke

POA



Description

Mercury Seapro 75HP Fourstroke - These commercial outboards are designed to work as hard as you do...engineered to be ultra tough working partners for anyone making their living on the water. Every SeaPro features unique components to cope with the additional demands of professional operation. Whatever your job there's a specific FourStroke or TwoStroke Mercury SeaPro model that's up to the task.

HP / kW	75 / 56
Engine type	8-valve single overhead cam (SOHC) Inline 4
Displacement (L)	2.1
Full throttle RPM	5000-5500
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	35 amp / 441 watt with water-cooled voltage regulator
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW 25W-40 Synthetic Blend
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Smart Start Electric
Controls	Mechanical throttle & shift
Steering	Big Tiller Dual Cable Mechanical Hydraulic
Shaft length	20" / 508 mm
Gearcase ratio	2.38:1
Dry weight *Lightest model available	363 lbs / 165 kg



Bore and stroke 3.5 x 3.2" / 90 x 81 mm
Ignition SmartCraft ECM 70 Digital Inductive
Fuel system Electronic Fuel Injection (EFI)
Cooling system Water-cooled with thermostat
Gear shift F-N-R
Trim system Power Tilt Power Trim
Exhaust system Through prop
Shallow water trim range (degrees) 20
Color Phantom Black
Lubrication system Integrated Dry Sump
Oil Capacity 5.5 qts / 5.2l
Maximum Trim Range 22° (-6° to 16°)
Maximum Tilt Range 70° (-6° to 64°)

