Mercury 90 HP EFI Fourstroke 19769.00



Description

Mercury 90 HP EFI Fourstroke - Unbridled power, unexpectedly compact, uncompromising reliability, unbelievable fuel efficiency. Unlike any other mid-range Fourstroke the world has ever seen.

HP / kW 90 / 66.2

Engine type 8-valve single overhead cam (SOHC) Inline 4

Displacement (L) 2.1

Full throttle RPM 5000-6000

Air induction Performance-Tuned Scroll Intake Manifold

Fuel induction system Computer Controlled Multi-Port Electronic Fuel Injection (EFI)

Alternator amp / Watt 35 amp / 441 watt with water-cooled voltage regulator

Recommended fuel Unleaded 91 RON Minimum

Recommended oil Mercury FourStroke Oil 10W-30

Engine protection operator warning system SmartCraft Engine Guardian

Compatible with SmartCraft digital technology Yes

Starting Smart Start Electric

Controls Mechanical throttle & shift

Steering Big Tiller Compatible Dual Cable Mechanical Hydraulic power steering

Shaft length 20" / 508 mm 25" / 635 mm

Gearcase ratio 2.07:1

Dry weight *Lightest model available 359 lbs / 163 kg

Emissions Star Rating 3

Bore and stroke 3.5 x 3.2" / 90 x 81 mm

Ignition SmartCraft ECM 70 Digital Inductive

Fuel system Electronic Fuel Injection (EFI)

Cooling system Water-cooled with thermostat

Gear shift F-N-R

Gearcase options Standard

Trim system Power Tilt Power Trim

Exhaust system Through prop

Shallow water trim range (degrees) 20

Color Phantom Black

Phone: (09) 271 1575

Email: sales@aucklandmarine.co.nz Website: https://www.aucklandmarine.co.nz/ 321 Ti Rakau Drive Burswood, Auckland 2013 NZ



Lubrication system Integrated Dry Sump

Oil Capacity 5.5 qts / 5.2 I

22° (-6° to 16°) Maximum Trim Range 70° (-6° to 64°) Maximum Tilt Range

Phone: (09) 271 1575 Email: sales@aucklandmarine.co.nz Website: https://www.aucklandmarine.co.nz/ 321 Ti Rakau Drive Burswood, Auckland 2013 NZ

