## Mercury Bravo I® Outboard POA



## **Description**

The Mercury Racing Lab Finished **Bravo I** propellers offer great planing performance, excellent mid-range speeds and awesome top end speeds for center console applications.

The vented Bravo I is geared toward cats and step bottom boats with high outboard engine heights. It is available in LH and RH rotations: 22", 24", 25", 26", 27", 28", 29", 30", 32", & 34" pitch. The vented Bravo I is Lab Finished with 1" vent holes for high horsepower Mercury OptiMax, Pro XS, XS and additional two stroke outboard applications running on performance Bass, Flats and Center Console boats.

For the Verado applications the vented Bravo I is not required, refer to the <u>Bravo I Verado & Erndrive propeller.</u> SPECIFICATIONS

Diameter 15 1/4"

Pitch 22", 24", 25", 26", 27", 28", 29", 30", 32", 34" & 36"

Rotation LH & RH

Finish Lab with vent holes

APPLICATIONS Designed to run 60+ MPH with excellent speed and handling For 200 - 300 HP outboards, performance Bass, Vee, cat hulls or dual, triple or quad set ups Vented Bravo I recommended for 2-Stroke outboards

Phone: (09) 271 1575

Email: sales@aucklandmarine.co.nz Website: https://www.aucklandmarine.co.nz/ 321 Ti Rakau Drive Burswood, Auckland 2013 NZ

