Mercury M8 Drive POA



Description ATURES Combines best features of the dry-sump NXT¹ & Six drives. Dry-sumped for maximum power-output. Delivers 35% more power capacity than the legendary Six drive. All-new surface piercing gearcase, packed with heavy-duty components, is designed specifically to handle the 1350's higher torque. New 5 & 6-blade CNC sterndrive propellers are designed with stamina to allow the engine to endure in both treacherous and ideal offshore conditions. Two inches shorter resulting in an overall lower center of gravity for improved handling and overall boat performance. All new dry sump hydraulic transmission to handle the 1350's massive torque. While the lower drive cavity is bathed in oil, a unique propshaft driven oil pump sprays the upper drive gears. This reduces internal friction, increasing performance.

SPECIFICATIONS


Max. Power Cap. 1350 hp Input torque rating of 1300 ft. lbs.

Lower Unit Design Dry Sump Drive & Transmission

Max. Prop Diameter 18 inches

Available Gear Ratios 1.69:1, 1.53:1, 1.40:1, 1.30:1 Proshaft Rotation Left Hand & Right Hand Rotation

Drive Weight (lbs./kg.) 280/127



Email: sales@aucklandmarine.co.nz Website: https://www.aucklandmarine.co.nz/ 321 Ti Rakau Drive Burswood, Auckland 2013 NZ

