Mercury MerCruiser 6.2L 300HP Inboard

POA



Description

Mercury MerCruiser 6.2L 300HP Inboard - Proven technology, rock-solid reliability and an unbeatable combination of performance and fuel efficiency.

HP / kW 300 / 224
Maximum RPM (WOT 5000-5400
Displacement (L) 6.2
Engine Type V8, 2-valve/cylinder pushrod
Bore & Stroke 4.0 x 3.75" / 101.6 x 95.25 mm
Fuel Requirement 90 RON 10% Ethanol Maximum Unleaded Regular 87 Octane Minimum (R+M/2)
Engine Control System SmartCraft PCM 112 Digital Inductive Standard SmartCraft with DTS
Fuel Delivery System Computer controlled Multi-Port Electronic Fuel Injection (MPI)
Starting Electric (turn-key) Smart Start Electric
Air Induction Performance-Tuned Scroll Intake Manifold
Ignition SmartCraft PCM 112 Digital Inductive
Alternator amp / Wat Fully regulated belt-driven 70 amp (882 watt)
Water Drain System Air Actuated "Season Extender"
Exhaust System Through transom
Cooling System Fresh water cooled (closed cooling)
Lubrication System Integrated wet sump
Recommended Oil NMMA Certified FCW 25W-40 Synthetic Blend
Engine Guardian System SmartCraft Engine Guardian
Gear shift F-N-R

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ

Transmission and Ratio	63 A: 1.216, 1.5:1, 2.0:1, 2.5:1 63 IV: 1.5:1, 2.0:1, 2.5:1
Dimensions (LxWxH) in	32 x 30 x 22" / 813 x 762 x 559 mm
Weight (engine only)	862 lbs / 391 kg

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ