Mercury MerCruiser 6.2L 350HP Inboard

POA



Description

Mercury MerCruiser 6.2L 350HP Inboard - Proven technology, rock-solid reliability and an unbeatable combination of performance and fuel efficiency.

HP / kW	350 / 261
Maximum RPM (WOT	5000-5400
Displacement (L)	6.2
Engine Type	V8, 2-valve/cylinder pushrod
Bore & Stroke	4.0 x 3.75" / 101.6 x 95.25 mm
Fuel Requirement	90 RON 10% Ethanol Maximum Unleaded Regular 87 Octane Minimum (R+M/2)
Engine Control System	SmartCraft PCM 112 Digital Inductive Standard SmartCraft with DTS
Fuel Delivery System	Computer controlled Multi-Port Electronic Fuel Injection (MPI)
Starting	Electric Smart Start Electric
Air Induction	Performance-Tuned Scroll Intake Manifold
Ignition	SmartCraft PCM 112 Digital Inductive
Alternator amp / Watt	Fully regulated belt-driven 70 amp (882 watt)
Water Drain System	Air Actuated "Season Extender"
Exhaust System	Through transom
Cooling System	Fresh water cooled (closed cooling)
Lubrication System	Integrated wet sump
Recommended Oil	NMMA Certified FCW 25W-40 Synthetic Blend
Engine Guardian System	SmartCraft Engine Guardian
Gear shift	F-N-R
Transmission and Ratio	63 A: 1.216, 1.5:1, 2.0:1, 2.5:1 63 IV: 1.5:1, 2.0:1, 2.5:1

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ

Dimensions (LxWxH) in	32 x 30 x 22" / 813 x 762 x 559 mm
Weight (engine only)	862 lbs / 391 kg

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ