Mercury MerCruiser T6200 Towsport Inboard

POA



Description

Mercury MerCruiser T6200 Towsport Inboard - A flawless blend of torque, pulling power, and launch propulsion.

HP / kW	320 / 239
Maximum RPM (WOT	5000-5400
Displacement (L)	6.2
Engine Type	V8, 2-valve/cylinder pushrod
Bore & Stroke	4.0 x 3.75" / 101.6 x 95.25 mm
Fuel Requirement	90 RON 10% Ethanol Maximum Unleaded Regular 87 Octane Minimum (R+M/2)
Engine Control System	SmartCraft PCM 112 Digital Inductive Mechanical Shifting with Optional SmartCraft DTS
Fuel Delivery System	Computer controlled Multi-Port Electronic Fuel Injection (MPI)
Starting	Electric (turn-key) Smart Start Electric
Air Induction	Performance-Tuned Scroll Intake Manifold
Ignition	SmartCraft PCM 112 Digital Inductive
Alternator amp / Watt	Fully regulated belt-driven 70 amp (882 watt)
Water Drain System	Air Actuated "Season Extender"
Exhaust System	Through transom
Cooling System	Water-cooled with thermostat Optional: Fresh Water Cooling (Closed Cooling)
Lubrication System	Integrated wet sump
Recommended Oil	NMMA Certified FCW 25W-40 Synthetic Blend
Engine Guardian System	SmartCraft Engine Guardian
Gear shift	F-N-R
Transmission and Ratio	45 C: 1.0:1 45 IV: 1.46:1

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ

Dimensions (LxWxH) in	32 x 30 x 22" / 813 x 762 x 559 mm

Weight (engine only)

862 lbs / 391 kg

Phone: (09) 271 1575
Email: sales@aucklandmarine.co.nz
Website: https://www.aucklandmarine.co.nz/
321 Ti Rakau Drive Burswood, Auckland 2013 NZ