

Suzuki 115HP 4 Stroke
\$20,749 FULLY FITTED



Description

TALK YOUR PERSONALISED DEAL: **OPTIONS.ZERO %.** INTEREST or **CASHBACK plus TRADE UP.** Be **QUICK ONLY WHILE STOCKS LAST.**

T'S & C'S APPLY.

MODEL DF115BTL

RECOMMENDED TRANSOM HEIGHT mm (in.) L: 508, X: 635

STARTING SYSTEM Electric

WEIGHT kg *1 L: 188, X: 192

ENGINE TYPE DOHC 16-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS 4

PISTON DISPLACEMENT cm3 (cu.in.) 2,045

BORE — STROKE mm (in.) 86 x 88

MAXIMUM OUTPUT kW (PS) 84.6

FULL THROTTLE OPERATING RANGE rpm 5,000-6,000

STEERING Remote

OIL PAN CAPACITY Lit. 5.5

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 40A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.59:1



GEAR SHIFT F-N-R

EXHAUST Through Prop Hub Exhaust

PROPELLER SELECTION (Pitch)*2 All propellers are the 3-blade type 15-25

