

Suzuki 15HP 4 Stroke

\$3875



Description

Short Shaft only available-LIMITED STOCK.

MODELDF 15A

RECOMMENDED TRANSOM HEIGHT mmS: 381, SHORT SHAFT ONLY AVAILABLE AT THIS PRICE.

STARTING SYSTEM Electric / Manual

WEIGHT kg *5S: 48, L: 49 / S: 44, L: 45

ENGINE TYPE OHC

FUEL DELIVERY SYSTEM Battery-Less Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS 2

PISTON DISPLACEMENT cm3327

BORE STROKE mm60.4x57

MAXIMUM OUTPUT kW11.0

FULL THROTTLE OPERATING RANGE rpm5,000-6,000

STEERING Tiller

OIL PAN CAPACITY Lit. (U.S. qt)1.0

FUEL TANK CAPACITY Lit.12

IGNITION SYSTEM Digital CDI

ALTERNATOR1 2V 12A / 12V 6A

ENGINE MOUNTING Shear Mount

TRIM METHOD Manual Trim and Tilt

GEAR RATIO 2.08:1

GEAR SHIFT F-N-R

Phone: (09) 271 1575

Email: sales@aucklandmarine.co.nz

Website: <https://www.aucklandmarine.co.nz/>

321 Ti Rakau Drive Burswood, Auckland 2013 NZ



EXHAUST Through Prop Hub Exhaust

PROPELLER SELECTION (Pitch) *5 All propellers are the 3-blade type7-12

Dry weight: not including propeller and engine oil

Please inquire at your local dealer for details of the propeller

The appearance, colors, and equipment of outboard motors may differ according to market and grade.

Specifications may change without prior notice.

*Manufacture data

