

Suzuki 225HP 4 Stroke

\$34,499 NOT FITTED



Description

TALK YOUR PERSONALISED DEAL: **OPTIONS.ZERO % INTEREST** or **CASHBACK plus TRADE UP. BE QUICK ONLY WHILE STOCKS LAST.**
T'S & C'S APPLY.

MODEL DF225TX 6 CYL

RECOMMENDED TRANSOM HEIGHT mm L: 508 *4, X: 635, XX: 762

STARTING SYSTEM Electric

WEIGHT kg *1 L: 264 *4, X: 275, XX: 284

ENGINE TYPE DOHC 24-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS V6 (55-degree)

PISTON DISPLACEMENT cm³ 3,614

BORE Å—STROKE mm 95 x 85

MAXIMUM OUTPUT kW 165.0

FULL THROTTLE OPERATING RANGE rpm 5,000-6,000

STEERING Remote

OIL PAN CAPACITY Lit. 8.0

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 54A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.29:1

GEAR SHIFT F-N-R

EXHAUST Through Prop Hub Exhaust

PROPELLER SELECTION (Pitch)*2

All propellers are the 3-blade type 15"-27.5"



