

Suzuki 300HP 4 Stroke

\$43,499 FULLY FITTED



Description

TALK YOUR PERSONALISED DEAL: **OPTIONS.ZERO % INTEREST** or **CASHBACK plus TRADE UP. BE QUICK ONLY WHILE STOCKS LAST.**

T'S & C'S APPLY.

MODEL DF300APX

RECOMMENDED TRANSOM HEIGHT mm X:635, XX:762

STARTING SYSTEM Electric

WEIGHT (KG) ** X: 290, XX: 299

ENGINE TYPE DOHC 24-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS V6 (55-degree)

PISTON DISPLACEMENT (cm3) 4,028

BORE X STROKE (mm) 98 x 89

MAXIMUM OUTPUT (kW) 220.7

FULL THROTTLE OPERATING RANGE (rpm) 5,700-6,300

STEERING Remote

OIL PAN CAPACITY (Lit.) 8

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 54A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.08:1

GEAR SHAFT F-N-R (Drive-by-wire)



EXHAUST Through Prop-Hub Exhaust

PLEASE NOTE: Price quoted does not include gauges, remotes and rigging kit. Please talk with our freindly sales staff.

