

SUZUKI 40HP 2 STROKE ELECTRIC/TILLER

\$6375



Description

MODEL DT40W

TRANSOM HEIGHT mm L: 508, L2: 559 S: 381, L: 508, L2: 559

STARTING SYSTEM Electric

WEIGHT kg L: 79 S: 74, L: 75, L2: 80

ENGINE TYPE 2-stroke 2 Cylinders

DISPLACEMENT cm³ 696

BORE Å—STROKE mm 79x71

MAXIMUM POWER kW 29.4

FULL THROTTLE OPERATING RANGE rpm 5,000-5,600

FUEL TANK CAPACITY Lit. Gasoline:25

IGNITION SYSTEM Suzuki P.E.I.

BATTERY CHARGING 12V 80W 12V 80W (Optional)

STEERING Tiller

TRIM METHOD Manual Trim & Tilt

FUEL/OIL MIXING RATIO 50:1 *1

GEAR SHIFT F-N-R

GEAR RATIO 2.09:1

DRIVE PROTECTION Rubber bush

PROPELLER SIZE in.*2

All propellers are the 3-blade type. 11-1/2Å—10, 11-1/2Å—11,

11-5/8Å—12, 11-1/2Å—13,

Phone: (09) 271 1575

Email: sales@aucklandmarine.co.nz

Website: <https://www.aucklandmarine.co.nz/>

321 Ti Rakau Drive Burswood, Auckland 2013 NZ



11-3/8" —14, 11-1/4" —15 Suzuki "C.C.I" oil or NMMA (National Marine Manufactures Association) certified TC-W3TM Oil Select the propeller which fits within the range of the engine rpm of each model

The appearance, colors, and equipment of outboard motors may differ according to market and grade.

Specifications may change without prior notice.

*Manufacture data TECHNOLOGY SPECIFICATIONS

