

Suzuki 60HP 4 Stroke

\$12,640.00



Description

Suzuki Repower with Suzuki

MODEL DF60A

RECOMMENDED TRANSOM HEIGHT mm S:381, L:508, X:635

STARTING SYSTEM Electric

WEIGHT kg *1 S:102, L:104, X:107

ENGINE TYPE DOHC 12-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS 3

PISTON DISPLACEMENT cm³ 941

BORE Å— STROKE mm 72.5 Å— 76

MAXIMUM OUTPUT kW 44.1

FULL THROTTLE OPERATING RANGE rpm 5,300-6,300

STEERING Electric

OIL PAN CAPACITY Lit. (U.S. qt) 2.7

FUEL TANK CAPACITY Lit. 25 (Optional)

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 27A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.27:1



GEAR SHIFT F-N-R

EXHAUST Through Prop Hub Exhaust

PROPELLER SELECTION (Pitch) *5 All propellers are the 3-blade type 9-17

