

# Suzuki 80HP 4 Stroke

**\$15,640.00**



## Description

Suzuki Repower with Suzuki

MODEL DF80A

RECOMMENDED TRANSOM HEIGHT mm (in.) L: 508, X: 635

STARTING SYSTEM Electric

WEIGHT kg \*1 L: 156, X: 160

ENGINE TYPE DOHC 16-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS 4

PISTON DISPLACEMENT cm<sup>3</sup> 1,502

BORE — STROKE mm 75 x 85

MAXIMUM OUTPUT kW 58.8

FULL THROTTLE OPERATING RANGE rpm 5,300-6,300

STEERING Remote

OIL PAN CAPACITY Lit. (U.S. qt) 4.0

IGNITION SYSTEM Fully-transistorized

FUEL TANK CAPACITY Lit. 25 (Optional)

ALTERNATOR 12V 27A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.59:1

GEAR SHIFT F-N-R

EXHAUST Through Prop Hub Exhaust



DRIVE PROTECTION Rubber Hub

PROPELLER SELECTION (Pitch) \*2 3 blades and 4 blades propeller are available. 13-23

