

Suzuki DF30 4 Stroke Outboard

\$8499.00



Description

Key Specifications (DF30ATHL)

Feature	Specification	Source
Engine Type	SOHC, 4-Valve, In-line 3-cylinder	
Maximum Output	30 HP (22.1 kW)	
Displacement	489 cc (29.8 cu. in.)	
Full Throttle RPM Range	5,300 - 6,300 RPM	
Fuel Delivery System	Battery-less Electronic Fuel Injection	
Starting System	Manual or Electric (model dependent)	
Oil Capacity	1.5 L (1.6 US qts)	
Gear Ratio	2.09:1	
Alternator	12V 14A	
Recommended Transom Height	S: 381 mm (15"), L: 508 mm (20")	
Weight	Varies by model (approx. 62-74 kg / 137-163 lbs)	

Key Features **Lean Burn Control System** This intelligent system predicts fuel needs based on operating conditions to deliver a leaner fuel mixture, significantly improving fuel efficiency. **Offset Crankshaft** The crankshaft is positioned slightly off-center of the cylinder bore to reduce lateral pressure, resulting in smoother piston movement and improved operating efficiency. **Roller Rocker Arms** The DF30A is the first in its class to use a roller with internal bearings on the cam surface for both intake and exhaust valves, which reduces friction. **Suzuki Anti-Corrosion System** A specialized finish protects the engine from damage in both fresh and saltwater environments. **Easy Start Recoil** In models with manual starting, a light recoil starter is incorporated, requiring less pull strength for quick and easy starting.

